

Patina Plus™ System – Technical Data Sheet

Issued by: Nautilus Innovation

Date: 25 July 2025

System Overview

The Patina Plus™ System is a 3-step surface care and weathering solution for exterior timber. It combines initial preparation, long-term silvering, and periodic maintenance using a coordinated product set developed and distributed by Nautilus Innovation.

Product Components

1. Timber Brightener – Prepares both new and aged timber by removing surface oxidation and embedded grime, restoring a clean and open grain ready for treatment.
2. Patina Plus™ – A proprietary single-application silicate treatment that promotes natural silver-grey weathering.
3. Dekloc™ Maintenance+ Wash – A mild powder-based cleaner for maintaining timber appearance over time.

System Application Steps

Step 1: Clean with Timber Brightener

- Apply Timber Brightener to clean new or weathered timber.
- Removes grime, tannin staining, and surface oxidation.
- Rinse thoroughly and allow to dry completely before proceeding.

Step 2: Apply Patina Plus™

- Apply evenly with brush, roller, or sprayer.
- Avoid rain exposure for at least 6 hours post-application.
- Visible silvering will develop progressively over 2–8 weeks.

Step 3: Periodic Maintenance (Every 2–3 Years)

- Use Maintenance+ Wash to clean timber surface gently without stripping Patina Plus™.
- Rinse well and allow surface to dry.

Recommended Use Cases

Exterior cladding, soffits, screens, fencing, and architectural timber elements exposed to the weather.

Coverage Rates (Approx.)

- Timber Brightener: 8–12 m² per litre
- Patina Plus™: 150–200 ml/m²
- Maintenance+ Wash: 10–15 m² per diluted kg

Storage and Packaging

- Store all products in sealed containers between 10–30°C
- Avoid direct sun and contact with incompatible materials
- Available in sample and bulk sizes (1L, 5L, 20L / 1–4.2kg buckets)

Safety and Handling

Use gloves and eye protection when handling. Do not ingest. For professional and project use only.